



ŁAŃCUCHY OGNIWOWE O OGNIWACH DŁUGICH WG NORMY: PN-M/84543/DIN 763

Nr kat.	Grub. ogniwa d	Podziałka t	Szer. ogniwa b	Nieobrabiany cieplnie		Obrabiany cieplnie		Masa kg/m	Norma	Norma zbliżona
				Obciąż. użytkowe kg	Siła zrywająca kN	Obciąż. użytkowe kg	Siła zrywająca kN			
R-1	4	32	16	100	4,0	—	—	0,27	PN-75/M-84543	DIN 763
R-2	5	36	20	160	6,4	—	—	0,43	PN-75/M-84543	DIN 763
R-3	6	42	24	200	8,0	—	—	0,63	PN-75/M-84543	DIN 763
R-4	8	54	32	400	16,0	—	—	1,10	PN-75/M-84543	DIN 763
R-5	10	66	40	625	25,0	1000	50	1,75	PN-75/M-84543	DIN 763
R-6	12	82	48	750	30,0	1300	80	2,45	W.T. - 003/97	—
R-7	13	82	50	1000	40,0	1600	100	2,95	PN-75/M-84543	DIN 763
R-8	14	80	52	1250	50,0	3750	140	3,60	ZN-77/O1 8-5027-1 31	—
R-9	16	80	57	1500	60,0	2500	180	4,70	W.T. -003/97	DIN 762
R-10	18	90	65	—	—	6250	250	6,00	W.T. - 004/97	DIN 762
R-11	22	120	87	90	180	-	-	-	TP 203-59-77	-